

<b>DC Battery Charger</b>							
Model	SKG12/ 10A	SKG12/ 20A	SKG12/ 30A	GCA 6A / 6 – 12VDC	GCA 10A / 6 – 24VDC	GCA 20A / 6 – 24VDC	GCA 30A / 6 – 24VDC
Input	Voltage Range	230VAC or 100VAC 1Ø +/- 10 %					
	Frequency Range	50Hz / 60Hz					
	Phase	Single Phase + Neutral + GND					
Output Voltage	13.8VDC	13.8VDC	13.8VDC	6-13.8VDC	6-27.6VDC	6-27.6VDC	6-27.6VDC
Display	Output Ampere Meter & LED			Output Ampere / Voltage Meter			
Type	Auto Charger			Commutate Charger			
Protection	Reverse Polarity, Over Charge, Fuse			Fuse			
Application Area	Automotive Repair Workshop, Generator Set, Shipping, Marine Vessel, PABX, Telecommunication						
Environment Temperature	Temperature 0 – 55°C Audible Noise (At 1Meter) < 45dB Humidity 10% - 90% (No Condensation)						
Gross Weight	5kg	7.5kg	10kg	4.3kg	7.2kg	13.6kg	15.2kg
Dimension (WxDxH)mm	205 x 170 x 130	245 x 200 x 140	245 x 200 x 140	195 x 155 x 150	205 x 280 x 160	205 x 360 x 280	
<b>DC Power Supply SK1700 (Scientific Type)</b>							
Model	SK1730SL1A-5A	SK1730SL10A-20A	SK1731SL1A-5A	SK1760SL1A-2A	SK1760SL3A-5A	SK1761SL1A-2A	SK1761SL3A-5A
Input Voltage	230VAC or 100VAC 1Ø +/- 10 % 50/60Hz						
Output Voltage	0-30VDC	0-60VDC	0-30VDCx2	0-30VDC	0-60VDC	0-30VDCx2	0-60VDCx2
Display	Digital LED x 2		Digital LED x 4	Digital LED x 2		Digital LED x 4	
Features	Adjustable Output Constant Voltage & Constant Current						
Protection	Limited Current & Short Circuit						
Application Area	Scientific Research, Education Institution, Electronics Repair Workstation, Electrical Workshop						
Environment Temperature	Temperature 0 – 55°C / Audible Noise (At 1Meter) < 45dB / Humidity 10% - 90% (No Condensation)						
Gross Weight	11kg	22kg	16kg	10kg	23kg	26kg	28kg
Dimension (WxDxH)mm	310 x 420 x 210	310 x 420 x 210	310 x 420 x 210	310 x 420 x 210	310 x 420 x 210	310 x 420 x 210	310 x 420 x 210
<b>DC Power Supply S-Series (Industrial Type)</b>							
Model	S10A / 0-30V	S30A / 0-30V	S10A / 0-60VDC	S80A / 0-60VDC	S100A / 0-150VDC	S100A / 0-300V	S100A / 0-500V
Input Voltage	230VAC or 100VAC 1Ø +/- 10 % 50/60Hz						
Output Voltage	0-30VDC	0-30VDC	0-60VDC	0-60VDC	0-150VDC	0-300VDC	0-500VDC
Display	One Channel - Digital LED x 2 OR Two Channel - Digital LED x 4						
Features	Output Constant Voltage, Current Adjustable, Regulation Voltage <0.05% / Current <0.1%						
Protection	Limited Current, Short Circuit & MCB						
Application Area	Education Institution, Electronics Factory, Railway Station, Electronics Repair Workstation						
Environment Temperature	Temperature 0 – 55°C Audible Noise (At 1Meter) < 45dB Humidity 10% - 90% (No Condensation)						
Efficiency	> 90%						
Gross Weight	18kg	28kg	23kg	110kg	350kg	510kg	660kg
Dimension (WxDxH)mm	180 x 320 x 390	190 x 250 x 465	190 x 360 x 465	500 x 1120 x 685	530 x 1245 x 775	685 x 1550 x 910	880 x 1770 x 1060
* For Custom Made DC Power Supply, The Specification, Size & Weight will be Changed or as User request as possible.							